



CENTRAL DKN - 25

CATEGORY : **TOUCH BUTTON CONTROLLED**

WERTE CENTRAL DKN-25 series has been developed, for to make longtime lubrication to the operations, which has requiring the 'drip system lubrication' such as sled and linear systems. The system, conveys the lubricant perfectly to the required point , through its proportional and progressive distributors. Provides the long-term and reliable liquid grease lubrication.

Recommended applications:

On the operations which has requiring the 'drip system lubrication'. Sled and linear systems.

Technical specifications:

Feeding voltage : 230 V. – 24 V. AC/DC

Operating voltage : 230 V.

Power consumption : 0,5 A.

Motor : 25 Watt.

Operating pressure : 2 ~ 16 Bar

Flow rate : 200 cc/min.

Operating temperature : -20°C ~ 80°C

Reservoir : 2,5 L.

Lubricant Viscosity : 50 ~ 260 cst.

Liquid grease viscosity : NLGI 000 ~ 00

Standard specifications :

Reservoir level switch, reservoir oil filter.

Suitable liquids:

Liquid grease

یکسال گارانتی و ۱۰ سال خدمات پس از فروش

آدرس دفتر مرکزی: تبریز - خیابان راه آهن - چهار راه قطران - پاساژ عمران - زیرزمین - پلاک ۳۲

تلفکس: ۳۴۳۹۱۴۴۹ - ۴۱۱۰۴۱۱ - تلفن همراه: ۰۹۱۴۴۱۴۲۴۳۲ - ۰۹۱۴۴۱۲۷۵۴۲

www.rhsahand.com - sale@rhsahand.com