



## CENTRAL PLC - 25

### CATEGORY : **PLC CONTROLLED**

WERTE CENTRAL PLC series lubrication systems has developed for to operate with the PLC command unit. The system, conveys the lubricant perfectly to the required point , through its proportional and progressive distributors. Provides the long-term and reliable liquid grease lubrication.

### **Recommended applications:**

On the operations which has requiring the 'drip system lubrication' and has PLC management system. PLC command Sled and linear systems.

## **Technical specifications:**

Feeding voltage : 230 V. – 24 V. AC/DC

Operating voltage : 230 V.

Power consumption : 0,5 A.

Motor : 25 Watt.

Operating pressure : 2 ~ 16 Bar

Flow rate : 200 cc/min.

Operating temperature : -20°C ~ 80°C

Reservoir : 2,5 L.

Lubricant Viscosity : 50 ~ 260 cst.

Liquid grease viscosity: NLGI 000 ~ 00

## **Standard specifications :**

Reservoir level switch, reservoir oil filter.

## **Suitable liquids:**

Liquid grease

# **یکسال گارانتی و ۱۰ سال خدمات پس از فروش**

آدرس دفتر مرکزی: تبریز - خیابان راه آهن - چهار راه قطران - پاساژ عمران - زیرزمین - پلاک ۳۲

تلفکس: ۳۴۳۹۱۴۴۹ - ۴۱۱ - تلفن همراه: ۰۹۱۴۴۱۴۲۴۳۲ - ۰۹۱۴۴۱۲۷۵۴۲

www.rhsahand.com - sale@rhsahand.com